



Model	Voltage	Watts	FLA	CFM	PSIG	Noise Level db(A)	Net Weight	
							kg	lbs
RPC100PT-1	1/60/115	530	w/a	3.5	100	w/a	33.5	69
RPC100PT-2	1/60/230	530	w/a	3.5	100	w/a	33.5	69
RPC100PT-3	1/50/220	530	w/a	3.2	100	w/a	33.5	69

*Refer to curves below for detailed performance data. Performance data and product specifications are subject to change without prior notice. Actual performance may vary by ±10%.

STANDARD FEATURES

- Compact rigid connecting rod
- Heat-releasing aluminum piston housing
- Cylinder hard-coated for long life
- Sturdy valve plate provides trouble-free, long service life
- Shock absorbing mounting feet
- Motor thermal protector included

- Capacitor start motor
- 4 pole AC motor
- High efficient cooling fan
- Fan cover prevents contact
- Special sealing cap for long life
- -4 to 40 Deg C ambient
- Open motor enclosure

ACCESSORIES

An air filter is required to obtain warranty coverage.



TECHNICAL DATA Available on line www.all-star-usa.com

If viewing this page online, just click on the links below

- Performance Temperature Rise Curves
- Standard Dimension Page
- Amperage
- Accessories
- Wiring Diagram

DIMENSIONS (Inch)			
	Length	Width	Height
Outside	13.7	13.7	23.6

Registered by one or more of these standards agency

