



Model	Voltage	Watt	FLA	CFM	“HG	Sound Level	Net Weight	
						db(A)	kg	lbs
RPV50D-12	12 VDC	250	12	3.3	26.7	65	6.8	14

*Refer to curves below for detailed performance data. Performance data and product specifications are subject to change without prior notice. Actual performance may vary by ± 10%.

STANDARD FEATURES

- Compact rigid designed connecting rod
- Heat-releasing designed aluminum die-cast piston housing
- Cylinder hard-coated treatment for long life
- Sturdy valve plate design provides trouble-free, long service life
- Shock absorbing mounting feet included

- DC brushless motor
- 2000 rpm motor speed
- High efficient cooling fan
- Fan cover prevents accidental contact
- Special sealing cap for long service life
- Quiet operation - below OSHA limits
- Suitable for operation in -4 to 40 Deg C ambient
- Open motor enclosure



ACCESSORIES

An air filter is required to obtain warranty coverage.

DIMENSIONS (Inch)			
	Length	Width	Height
Outside	8.6	5.0	7.87
Mounting	7.4	3.5	-0-

TECHNICAL DATA Available on line www.all-star-usa.com

If viewing this page online, just click on the links below

- Performance Temperature Rise Curves
- Standard Dimension Page
- Amperage
- Accessories
- Wiring Diagram

Registered by one or more of these standards agency

