



Model	Voltage	Watts	FLA	CFM	"HG	Sound Level		Net Weight	
						db(A)	kg	lbs	
RPVH150-1	1/60/115	370	w/a	2.8	29.5	w/a	9.8	22	
RPVH150-2	1/60/230	370	w/a	2.8	29.5	w/a	9.8	22	
RPVH150-3	1/50/220	370	w/a	2.3	29.5	w/a	9.8	22	

*Refer to curves below for detailed performance data. Performance data and product specifications are subject to change without prior notice. Actual performance may vary by ±10%.

STANDARD FEATURES

- Compact rigid connecting rod
- Heat-releasing piston housing
- Cylinder hard-coated for long life
- Sturdy valve plate provides long service life
- Shock absorbing mounting base
- Motor thermal protector included
- Capacitor start motor
- 4 pole AC motor
- High efficient cooling fan
- Fan cover prevents contact
- Special sealing cap for long service life
- -4 to 40 Deg C ambient
- Open motor enclosure



ACCESSORIES

An air filter is required to obtain warranty coverage.

TECHNICAL DATA

[Available on line www.all-star-usa.com]

If viewing this page online, just *click on the links below*

- Performance Temperature Rise Curves
- Standard Dimension Page
- Amperage
- Accessories

DIMENSIONS (Inch)			
	Length	Width	Height
Outside	9.8	6.0	7.8
Mounting	8.0	3.5	M6

Registered by one or more of these standards agency

