



Model	Voltage	Watt	FLA	CFM	“HG	Sound Level	Net Weight	
						db(A)	kg	lbs
RPV300-3	1/50/220	1500	3.8	10.6	29	79	35	17

\*Refer to curves below for detailed performance data. Performance data and product specifications are subject to change without prior notice. Actual performance may vary by ±10%.

**STANDARD FEATURES**

- Compact rigid connecting rod
- Heat-releasing aluminum piston housing
- Cylinder hard-coated treatment for long life
- Sturdy valve plate provides trouble-free, long service life
- Shock absorbing mounting feet
- Motor thermal protector

- Capacitor start motor
- 4 pole AC motor
- High efficient cooling fan
- Fan cover prevents contact
- Special sealing cap for long life
- -4 to 40 Deg C ambient
- Open motor enclosure

**ACCESSORIES**

An air filter is required to obtain warranty coverage.



**TECHNICAL DATA** Available on line [www.all-star-usa.com](http://www.all-star-usa.com)

If viewing this page online, just *click on the links below*

- Performance Temperature Rise Curves
- Standard Dimension Page
- Amperage
- Accessories
- Wiring Diagram

DIMENSIONS (Inch)			
	Length	Width	Height
Outside	12.5	6.2	12.4
Mounting	9.7	5.0	M8

Registered by one or more of these standards agency

