



Model	Voltage	Watt	FLA	CFM	"HG	Sound Level	Net Weight	
						db(A)	kg	lbs
RPVL30-1	1/60/115	180	w/a	2.1	25.9	w/a	8.5	19
RPVL30-2	1/60/230	180	w/a	2.1	25.9	w/a	8.5	19
RPVL30-3	1/50/220	180	w/a	1.7	28.9	w/a	8.5	19

*Refer to curves below for detailed performance data. Performance data and product specifications are subject to change without prior notice. Actual performance may vary by ±10%.

STANDARD FEATURES

- Compact rigid connecting rod
- Heat-releasing aluminum piston housing
- Cylinder hard-coated for long life
- Sturdy valve plate provides trouble-free, long service life
- Shock absorbing mounting feet
- Motor thermal protector

- Capacitor start motor
- 4 pole AC motor
- High efficient cooling fan
- Fan cover prevents contact
- Special sealing cap for long
- -4 to 40 Deg C ambient
- Open motor enclosure



ACCESSORIES

An air filter is required to obtain warranty coverage.

TECHNICAL DATA Available on line www.all-star-usa.com

If viewing this page online, just *click on the links below*

- Performance Temperature Rise Curves
- Standard Dimension Page
- Amperage
- Accessories
- Wiring Diagram

DIMENSIONS (Inch)			
	Length	Width	Height
Outside	14.5	6.7	10.0

Registered by one or more of these standards agency

